SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Acid Alcohol Decolorizer

SYNONYMS: Acid Alcohol Solution

CATALOG CODES: VAA
MANUFACTURER: Volu-Sol

ADDRESS: 5095 West 2100 South

Salt Lake City, UT 84120

 EMERGENCY PHONE:
 (800) 535-5053

 OTHER CALLS:
 (801) 974-9474

 FAX:
 (801) 974-9553

 CHEMICAL FAMILY:

 CHEMICAL FORMULA:

 PREPARED BY:
 Volu-Sol

RECOMMENDED USE: Laboratory chemical

RESTRICTIONS ON USE: Use as recommended

SECTION 2: HAZARD(S) IDENTIFICATION

EMERGENCY OVERVIEW:

GHS Classification: Flammable Liquids (Category 2)
Skin Irritation (Category 2)
Eye Irritation (Category 2A)

GHS LABEL ELEMENTS:

Pictogram:

Signal Word: Da Hazard Statement(s):

H225 Highly flammable liquid and vapour
H315 Causes skin irritation
H319 Causes serious eye irritation

Precautionary Statement(s):

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking

P233 Keep container tightly closed
P240 Ground/bond container and receiving equipment

P240 Ground/bornd container and receiving equipment

P241 Use explosion-proof electrical/ ventilating/
lighting/ equipment

P242 Use only non-sparking tools

P243 Take precautionary measures against static

discharge

P264 Wash skin thoroughly after handling

P280 Wear protective gloves/ eye protection/ face

protection

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately

all contaminated clothing. Rinse skin with

water/shower

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several

minutes. Remove contact lenses, if present and

easy to do. Continue rinsing

P321 Specific treatment (see supplemental first aid

instructions on this label)

P332+P313 If skin irritation occurs: Get medical advice/

If eye irritation persists: Get medical advice/ attention

P362 Take off contaminated clothing and wash before

reuse

P370+P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam for extinction
P403+P235 Store in a well-ventilated place. Keep cool

P501 Dispose of contents/container to an approved

waste disposal plant

OTHER HAZARDS: -

P337+P313

HMIS Classification:

Health hazard: 3
Chronic health hazard: Flammability: 3
Physical hazards: 0

NFPA Rating:

Health hazard: 3
Fire: 3
Reactivity Hazard: 0

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT	CAS NO. EC-NO. Index-NO.	
Ethanol (60-100%)	64-17-5 200-578-6 603-002-00-5	
Hydrochloric Acid (1-5%)	7647-01-0 231-595-7 017-002-01-X	

SECTION 4: FIRST AID MEASURES

INHALATION: If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician

INGESTION: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician

SKIN: Wash off with soap and plenty of water. Consult a physician

EYE: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. Continue rinsing eyes during transport to hospital

SECTION 5: FIRE-FIGHTING MEASURES

FLAMMABLE LIMITS IN AIR: Percentage by Volume

Upper: -% Lower: -%

FLASH POINT:

AUTOIGNITION TEMPERATURE:

EXTINGUISHING MEDIA: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide

FIRE FIGHTING PROCEDURES: In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full face piece operated in the pressure demand or other positive pressure mode

FIRE AND EXPLOSION HAZARDS: Use water spray to cool unopened containers

SECTION 6: ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE MEASURES: Use personal protective equipment. Avoid breathing vapours, mist, or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations. Dispose of in accordance with local regulations. US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The number to contact the US Coast Guard National Response Center is (800) 424-8802

SECTION 7: HANDLING AND STORAGE

HANDLING AND STORAGE: Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Use explosion-proof equipment. Keep away from sources of ignition. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Containers of this material may be hazardous when empty since they retain product residues (vapours, liquid); observe all warnings and precautions listed for the product. Take measures to prevent the buildup of electrostatic charge. No smoking

INCOMPATIBILITES: Peroxides

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE LIMITS: Reported in a time-weighted average (TWA)

Component	CAS-No.	Reference	OSHA		ACGIH	
			ppm	mg/m³	ppm	mg/m³
Ethanol 64-	64-17-5	1,000	1,900	1,000	1,900	
			PEL	PEL	TLV	TLV
Hydrochloric acid 7647	7647.04.0	7647.04.0	5	7	2	3
	7647-01-0		PEL	PEL	TLV	TLV

VENTILATION SYSTEM: Local and/or general exhaust is recommended to keep exposure below limits. Local exhaust ventilation is preferred for control of the emissions at its source, preventing dispersion into the general work area. Please refer to the ACGIH document, *Industrial Ventilation: A Manual of Recommended Practices*, for details

PERSONAL RESPIRATORS: If exposure limit is exceeded and engineering controls are not feasible, a half-face organic vapour respirator may be worn for up to ten times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier; whichever is lowest. A full-face piece organic vapour respirator may be worn up to 50 times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. For emergencies or instances where the exposure levels are not known, use a full-face, positive-pressure, air-supplied respirator. WARNING: Air-purifying respirators do not protect workers in oxygen-deficient atmospheres

SKIN PROTECTION: Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands

EYE PROTECTION: Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166 (EU)

BODY PROTECTION: Wear impervious clothing, Flame retardant antistatic protective clothing, the type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

 APPEARANCE:
 liquid

 ODOR:

 SOLUBILITY:

 pH:

 BOILING POINT:

 MELTING POINT:

 VAPOR PRESSURE:

 SPECIFIC GRAVITY:

 MOLECULAR WEIGHT:

 DENSITY:

SECTION 10: STABILITY AND REACTIVITY

CHEMICAL STABILITY: Stable under recommended conditions of use and

storage

CONDITIONS TO AVOID: Moisture, heat, flames, ignition sources

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: No data available

SECTION 11: TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION:

Acute Toxicity: No data available
Skin/Eye Irritation: No data available
Carcinogenicity: IARC: 3 – Group

IARC: 3 - Group 3: Not classifiable as to its

carcinogenicity to humans (Hydrochloric acid)

ROUTES OF ENTRY: Inhalation/Ingestion/Skin

SECTION 12: ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION:

Toxicity: No data available

Persistence and degradability: No data available

Mobility in soil: No data available

PBT/vPvB Results: PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Whatever cannot be saved for recovery or recycling should be handled as hazardous

waste and sent to a RCRA approved incinerator or disposed in an RCRA approved waste facility. Processing, use, or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state, and local requirements. Dispose of as unused product

SECTION 14: TRANSPORT INFORMATION

US DOT	IATA	IMDG/IMO
Shipping Name: Ethanol solutions	Shipping Name: Ethanol solution	Shipping Name: ETHANOL SOLUTION
Hazard Class:	Hazard Class: 3	Hazard Class: 3
UN Number: 1170	UN Number: 1170	UN Number: 1170
Packing Group:	Packing Group: II	Packing Group: II

SECTION 15: REGULATORY INFORMATION

	/ /
SARA 302	
SARA 313	7647-01-0
SARA 311/312 Hazards	Fire hazard, Acute Health Hazard, Chronic Health Hazard
State	Right to know lists: MA: 64-17-5, 7647-01-0 PA: 64-17-5, 7647-01-0, 7732-18-5 NJ: 64-17-5, 7647-01-0, 7732-18-5 California Prop. 65 Components: -

SECTION 16: OTHER INFORMATION

Disclaimer: The information is provided without any representation or warranty, express or implied, regarding the accuracy or correctness. The conditions or methods of handling, storage, use, and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage, or expense arising out of or in any way connected with the handling, storage, use, or disposal of the product.